





Advance & Convenience

High productivity and easy-to-use chain stitch machine

Electric Presser Foot Lifter

Presser foot is automatically lifted/dropped after sensor detect material. It increases productivity.



3 **Built-in Direct Drive Motor**

Powerful and electricity save.



2 Automatic Tape Cutter

A thread chain is automatically cut after sensor detect material. It increases operational efficiency.



Lint Collector (Option) 4

A thread chain and/or material after cut is sucked by air suction.



Model Subclass	N21A-W020	N31A-5030	N31A-5050	N31A-6030	
Fabric weight	Light / Medium	Medium / Heavy	Heavy	Medium / Heavy	
Max. speed (sti/min)	6,500	6,000	5,500	6,000	
No. of needles	2	2	2	3	
No. of threads	4	5	5	6	
Needle space (mm)	2	5	5	3+2	
Overedge width (mm)	4	5	6	4	
Stitch length (mm)	0.7-4.0	0.7-4.0	1.0-4.6	0.7-4.0	
Diff. feed ratio (mm)	0.7-1.7	0.7-1.7	0.8-1.5	0.7-1.7	
Presser foot lift (mm)	5.5	5.5	7.0	5.5	
Needles	DCx27 #11	DCx27 #14	DCx27 #19	DCx27 #11	

Other gauges can be available in market.

brother



-Photographs are for illustration purpose. They may not represent actual operating conditions and may display optional parts.

CHINA	BROTHER MACHINERY SHANGHAI LTD.	https://www.brother.cn/	+86-21-3135-3355
ASIA	BROTHER MACHINERY (ASIA) LTD.	https://www.brother.com.hk/	+852-2777-0010

BROTHER INDUSTRIES, LTD.

1-5, Kitajizoyama, Noda-cho, Kariya-shi, Aichi 448-0803, Japan. Phone: 81-566-95-0088 Fax: 81-566-25-3721 https://industrialsewingmachine.global.brother/ www.brotherearth.com